## SSDMD (SD Card to SATA Adapter)

The SSDMD support SD memory cards in a 2.5" SATA HDD form-factor to act as a solid state 2.5" SATA HDD. It supports SDXC up to 2TB capacity and UHS1 200MHz bus speed. SSDMD embedded two SD host controllers can provide flexible configurations like string mode and RAID0 functions.



# **Specification**

- Standard 2.5" SATA HDD interface
- Provides 2 expansion slots,
- Support SDSC/SDHC/SDXC card
- Support SATA 1.5G transfer rate
- No driver required

## System Requirements

Support all operating systems

Notebook or desktop computer with a free SATA port



**SSDMD** 



### SSDMD Package Content

- SSDMD (SD Card to SATA Adapter) x1
- Screw x4

#### SSDMD module Package Content

- SSDMD module (SD Card to SATA Adapter) x1
- Standard Height PCI express bracket x1

As a New manufacturer of quality computer connectivity products since 2009/Mar, BPLUS technology brings to market a broad range of upgrade products. These products bridge the connection between Desktop/Notebook systems and external peripherals.



#### Test Report:

Single Slot	SSDMD v1 Evaluation			Windows XP(SP3) Dell Vostro200			hd_speed			
2011/9/1							256 sector/co			
Card	Speed	Slot	Read	LT	RT	НТ	Write	LT	RT	НТ
Panasonic 8GB (old)	SDR104	0	56MBs	OK	OK	ОК	17.2MBs	OK	ОК	OK
		1	56MBs	ОК	OK	ОК	17.3MBs	OK	ОК	OK
Toshiba Black 64GB	SDR104	0	50.5MBs	ОК	OK	ОК	30MBs	OK	ОК	OK
		1	52MBs	ОК	OK	ОК	30MBs	OK	ОК	ОК
Toshiba Blue 16GB	SDR104	0	74MBs	ОК	OK	ОК	50MBs	ОК	ОК	ОК
		1	74MBs	ОК	OK	ОК	50MBs	OK	ОК	OK
San Disk 16GB	SDR50	0	36.5MBs	ОК	OK	ОК	28.3MBs	OK	ОК	ОК
		1	37MBs	ОК	OK	ОК	28.3MBs	OK	ОК	ОК
Green House	SDR50	0	32.5MBs	ОК	OK	ОК	16MBs	OK	ОК	ОК
		1	32MB	ОК	OK	NG	16MBs	OK	ОК	OK*
Panasonic 4GB	HS	0	21MBs	ОК	OK	ОК	15MBs	OK	ОК	ОК
		1	20.9MBs	ОК	OK	ОК	15MBs	OK	ОК	ОК
* 5V input LT: Low temp., RT: Room Temp., HT: High temp.										

			_		
*1	Need	to c	hange	sampling	clock

Stripping (Raid 0) 2011/9/1	SSDMD v1 Evaluation			Windows XP(SP3)  Dell Vostro200			hd_speed 256 sector/command			
Card	Speed		Read	LT	RT	НТ	Write	LT	RT	НТ
Panasonic 8GB (old) x2	SDR104		70MBs	OK	OK	OK	28MBs	ОК	OK	OK
Toshiba Black 64GB x2	SDR104		73MBs	OK	OK	ОК	38MBs	OK	OK	ОК
Toshiba Blue 16GB x2	SDR104		79MBs	OK	OK	OK	52MBs	ОК	OK	ОК
San Disk 16GB x2	SDR50		42.5MBs	OK	OK	OK	32.5MBs	ОК	OK	ОК
* 5V input	LT: Low temp., RT: Room Temp., HT: High temp.									

